



Premium Vinyl Silk – Data Sheet

Description:

Premium Vinyl Silk is a premium quality low sheen finish designed for use on all interior surfaces including wet areas. Its unique formulation incorporates speciality additives that improve washability and water resistance. **Premium Vinyl Silk** is easy to apply and when fully dry has excellent coverage.

Physical Properties

Resin Type:	Modified Vinyl
Solvent:	Water
Colour:	White, and full range of tinted colours
Finish:	Low Sheen
Drying time:	1 hour @ 18°C
Recoat time:	2 hours @ 18°
Dry Film Thickness:	50µ minimum
No. of coats:	2, some colours may require a 3 rd coat
Theoretical Coverage:	13m ² /litre per coat to attain 50µ
Primer Needed:	Recommended
Thinning & Cleaning:	Thin as required, cleanup with water

Performance:

- Excellent adhesion to **Everest** primers and undercoats.
- Good coverage when correctly applied.
- Easy to apply.
- May be used as an exterior finish when applied over the appropriate undercoat.

Limitations:

- Do not apply when temperature is below or expected to fall under 10°C.
- More than 2 coats maybe necessary when applying over porous fillers and sealers.
- Must be used in conjunction with an undercoat on unpainted exterior surfaces.
- Must be lightly sanded if more than 5 days between 1st and any following coats.
- May not be suitable for some commercial interiors.

Substrate Preparation:

Ensure all surfaces are clean, dry and dust free. Washing pre-painted surfaces with Sugar Soap is recommended. Old enamels and varnishes should be primed with **High Adhesion Primer**.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Commercial Coating Manufacturers Ltd makes no representation as to the completeness and accuracy thereof. In no event will Commercial Coating Manufactures Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.

Application:

Premium Vinyl Silk may be applied by brush, roller, speed brush or spray. Thinning with water is only recommended for spray application.

Although the information and recommendations set down here in this document are presented in good faith and believed to be correct, Commercial Coating Manufacturers Ltd makes no representation as to the completeness and accuracy thereof.
In no event will Commercial Coating Manufacturers Ltd be responsible for damages of any nature what so ever resulting from the use or reliance upon this information. No representations or warranties expressed or implied or merchantability, fitness for purpose or any other nature are made hereunder with respect to information or the product to which the information or Technical Data Sheet refers.